



Ballgame Tile „Jump“



	Ballgame Tile „Jump30“	Ballgame Tile „Jump40“
Dimensions	1010 x 1010 mm	1010 x 1010 mm
Thickness	30 mm	40 mm
Weight	29 kg	38 kg
Material	Polyurethane bound rubber granules, surface material is high quality black EPDM-Rubber-Granules	
Standard Colours	Redbrown, (coloured black granules), black	
Surface		Flat with no design
Underside		Flat w/ water drainage channels

Places of use: Football-Fields, Basketball-Fields

Benefits: anti-slip, minimized injury risk, noise reduction, water drains through the tile resulting in quick dry-time after rain, good bouncing quality

Installation: 30 mm-Version should be installed on asphalt, cement or pavement by completely gluing the tile to the ground. 40 mm-Version: same as 30 mm-Version or side-to-side gluing on crushed gravel. Use a jig saw to cut the tiles. Rubber will expand and shrink with temperature and humidity changes. Tolerances of material must be taken into consideration prior to all installations. Pay attention to installation guidelines.

Appropriate Glue: Type 1174 for ground gluing - Type SH100 for side to side gluing. Amount of glue needed: Ground gluing with 1174: app. 400 gr. / m². Side-to-side gluing with SH100: app. 30 gr. / meter.

Tolerances and note about material: *Tolerances in thickness: +/- 3 mm, *Tolerances in measurement: +/- 2 %

Rubber-Tiles will expand and shrink with changes in temperature and humidity. This reaction can be prevented by fully adhering the tiles to the ground (on bound sub grounds, cement, asphalt, ...). Use appropriate surroundings to keep area in place (e.g. stone-pavers or rubber-curbs).

We reserve the right to improve the products. July 2007

Siemensring 25
53925 Kall
Germany

Tel. +49 (0)2441 5037
Fax +49 (0)2441 5039

info@err-team.de

more ...
Information,
examples of use,
installation guidelines &
Tips at:

www.err-team.de