

**Rubber-H-Blocks „Luxus“**

<b>Dimensions</b>	200 x 160 mm
<b>Thickness</b>	40 mm
<b>Weight</b>	35 kg / m <sup>2</sup>
<b>Material</b>	Polyurethane bound rubber granules and buffings
<b>Standard Colour</b>	redbrown
<b>Special Colours</b>	green and black

<b>Water-permeable</b>	Yes, though most of the water will drain between the pavers.
------------------------	--

<b>Requirements</b>	Crushed gravel (top layer app. 2 – 8 mm) or asphalt, cement (slope of 1-2 % recommended)
---------------------	--

**Places of use:** walkways, paddocks, guiding-circles, roundpen, stall aisles

**Benefits:** highly compressed material, extremely durable and anti-slip, even at high and low temperatures, elegant optic, soft to the joints

**Installation:** Use a fixed border around the area where pavers are laid. Pavers are laid loose on crushed gravel, compact gravel prior to laying material. Do not compact afterwards. Gluing on bound subgrounds as asphalt or cement is possible. Cut by using a fret saw,

**Tolerances and note about material:** Tolerances and note about material: \*Tolerances in thickness: +/- 3 mm, \*Tolerances in measurement: +/- 2%. Rubber-Pavers can expand and shrink with changes in temperature and humidity.

*We reserve the right to improve the products. July 2007*

Siemensring 25  
53925 Kall  
Germany

Tel. +49 (0)2441 5037  
Fax +49 (0)2441 5039

info@err-team.de

more ...  
Information,  
examples of use,  
installation guidelines &  
Tips at:

[www.err-team.de](http://www.err-team.de)