

Horsetiles „HT“



	„HT42“	„HT60“
Dimensions	1010 mm x 1010 mm	1010 mm x 1010 mm
Thickness	42 mm	60 mm
Weight	33 kg	44 kg
Material	Polyurethane bound rubber granules	
Standard Colours	Redbrown or Black-mixcoloured	
Surface-Design	Flat	
Underbody	„Feet-Structure“, similar to the design of an egg-carton	
Water-permeable	Yes. Urine and water are able to drain through the hundreds of canals in the mat.	
Requirements	Bound subground (e.g. asphalt, cement, ...), slope of min. 3%, any sort of drainage	
Cleaning-interval	Depending on the amount of dirt on and especially under the mats, they need to be cleaned in regular intervals (at least twice a year from both sides). Remove all loose dirt under the mats and let a fair amount of water soak through the mats using a garden hose or a high pressure cleaner. Put the cleaner to medium strength only. Allow some hours for drying afterwards.	

Places of use: paddock, stall, roundpen, wash rack

Installation/Assembling: The mats are installed loose in stalls - the weight of the mats and the walls will hold the mats in place. Mats can be cut with a hand held utility knife or better with a fret-saw. Due to the possible change in dimension (due to change in temperature and humidity) cutting may be necessary after some time.

Tolerances and note about material: *Tolerances in thickness: +/- 2 mm, *Tolerances in measurement: +/- 2 %. Rubber-Tiles expand under warm conditions and shrink in cold conditions. When the expanding leads to bending of the tiles they have to be shorted by some cm at 2 sides of the area (see separate installation sheet).

We reserve the right to improve the products. July 2007

Siemensring 25
53925 Kall
Germany

Tel. +49 (0)2441 5037
Fax +49 (0)2441 5039

info@err-team.de

more ...
Information,
examples of use,
installation guidelines &
Tips at:

www.err-team.de