



PU-Glue 1174



Format	1,1 kg bottles
Colour	Milky-cloudy
Needed tools	No tools are needed to use „1174“. Directly use out of bottle by squeezing gently.
Characteristics	Moisture curing Polyurethane Glue for gluing of rubber granule tiles and safety-elements on bound sub grounds (cement, asphalt, ...) or for side to side gluing of such products.
Min. Temperature for use:	10 Degrees Celsius
Viscosity	More liquid at higher, less liquid at lower temperatures
Precautions:	Use appropriate gloves. Safety-Data-Sheets are supplied upon request.

Places of use:

Gluing of porous Rubber-Tiles and safety elements. On porous, difficult grounds: use Primer 1103 first.

Similar / further Products:

Due to its higher viscosity the glue SH100 is better suited for side-to-side gluing

Installation:

Suitable for gluing of porous Rubber-Tiles and safety elements. Do not spill glue on product – remove immediately using a soft cloth. Dried glue turns yellow and is very hard to remove. See installation sheet for details

TOLERANCES AND NOTE ABOUT MATERIAL:

Never to be used in connection with any kind moisture (e.g. rain, frost, fog, ...) Not to be used at temperatures of less than 10 Degrees Celsius. Contains Diphenylmethan-4,4'Di-Isocyanat. Use within 6 month – see bottle label.

We reserve the right to improve the product. July 2007

Siemensring 25
53925 Kall
Deutschland

Tel. +49 (0)2441 5037
Fax +49 (0)2441 5039

info@err-team.de

more ...
Information,
examples of use,
installation guidelines &
Tips at:

www.err-team.de