

**PU-Glue SH100**

<b>Format</b>	0,31 kg tubes
<b>Colour</b>	grey
<b>Needed tools</b>	Glue-gun
<b>Characteristics</b>	Moisture curing Polyurethane Glue especially suited for side-to-side gluing of rubber granule tiles and safety-elements
<b>Min. Temperature for use:</b>	5 Degrees Celsius
<b>Viscosity</b>	similar to a thick paste
<b>Precautions:</b>	Use appropriate gloves. Safety-Data-Sheets are supplied upon request.

**Places of use:** Side-to-Side-Gluing of porous Rubber-Tiles and safety elements.

**Similar / further Products:**

To fully adhere tiles to a bound subground (eg. Cement, asphalt) we recommend the glue 1174.

**Installation:**

Suitable for gluing of porous Rubber-Tiles and safety elements. Do not spill glue on product – remove immediately using a soft cloth.

Pay attention to our installation sheet.

**TOLERANCES AND NOTE ABOUT MATERIAL:**

Never to be used in connection with any kind moisture (e.g. rain, frost, fog, ...) Not to be used at temperatures of less than 5 Degrees Celsius. Use within 6 month.

*We reserve the right to improve the product. July 2007*

Siemensring 25  
53925 Kall  
Deutschland

Tel. +49 (0)2441 5037  
Fax +49 (0)2441 5039

info@err-team.de

more ...  
Information,  
examples of use,  
installation guidelines &  
Tips at:

[www.err-team.de](http://www.err-team.de)