

Rubber-Curb

Dimensions	length: 1010 mm, height: 200 mm, strength: 80 mm
-------------------	--

Weight	14 kg / pcs.
---------------	--------------

Material	Polyurethan bound rubber granules
-----------------	-----------------------------------

Standard Colours	redbrown, green (coloured black granules), black
-------------------------	--

Special Colours 1	Blue, grey (coloured black granules)
--------------------------	--------------------------------------

Surface	Bevel on the long side
----------------	------------------------

Places of use: Around Safety-Tile-Areas and Sport-Areas,

Installation: „Rubber Curb (Rubber-Safety-Edge)“ is laid into fresh cement. The bottom line on the stone should be covered with cement at least by 2 cm. Cut by using a fret saw with a smooth blade.

Pay attention to measurement tolerances prior to and while assembling.

Rubber tiles can be glued to the curb by using PU-Glue 1174 or SH100.

TOLERANCES AND NOTE ABOUT MATERIAL:

*Tolerances in thickness: +/- 2 mm, *Tolerances in measurement: +/- 2 %
 Rubber-Safety-Elements expand under warm conditions and shrink in cold conditions.
 Pay attention to installation guidelines.

We reserve the right to improve the product. July 2007

Siemensring 25
 53925 Kall
 Deutschland

Tel. +49 (0)2441 5037
 Fax +49 (0)2441 5039

info@err-team.de

more ...
 Information,
 examples of use,
 installation guidelines &
 Tips at:

www.err-team.de