

Safety-Tiles



	Standard 25	Standard 42	Standard 60	Standard 85
Dimensions	1010 mm x 1010 mm			
Thickness	25 mm	42 mm	60 mm	85 mm
Weight	22 kg	29 kg	42 kg	52 kg
Critical Fallheight (DIN/EN 1177)	0,90 m	1,45 m	2,00 m	2,80 m
Material	Polyurethane bound rubber granules, surface material is high quality black EPDM-Rubber-Granules			
Standard Colours	Redbrown, (coloured black granules), black			
Special Colours 1	green, blue, grey (coloured black granules)			
Special Colours 2	EPDM colours – or mix of such – see colour list			
Surface Design	Cruciform-Design (optical effect of 50 x 50 cm tiles)			
Special Design	Brick-effect, H-Block, No-Design,			
Underbody	„Feet-Structure“, similar to the design of an egg-carton if strength is 42 mm or more. The 25 mm version has a flat structure with water-drainage-channels			

Places of use: Playgrounds, Jump-Castles, Climbing-Walls, around table-tennis, ...

Installation of 42, 60 and 85mm tiles: „Standard“ ideally is to be fully adhered to the substrate (cement, asphalt, H-Blocks). On crushed gravel: Glue side to side with PU-Glue SH100 or other appropriate glue. Cutting by hand held utility knife or electric hand saw with a smooth blade. Pay attention to measurement tolerances prior to and while assembling. Recommended PU-glue: Type 1174 or SH100. Amount of glue needed: Fully adhered: app. 350 gr. / m², Side to side glueing with SH100: app. 30 gr. / meter. Pay attention to installation-sheet.

Installation of 25mm tiles: „Standard 25“ must be fully adhered to the ground (cement, asphalt, H-Blocks). Placing Standard 25 on crushed gravel or sand is not recommended. Recommended PU-glue: Type SH100. Amount of glue needed: app. 30 gr. / meter. Pay attention to installation-sheet.

Tolerances and note about material: *Tolerances in thickness: +/- 3 mm, *Tolerances in measurement: +/- 2 %
Rubber-Tiles expand under warm conditions and shrink in cold conditions. This reaction can be prevented by fully adhering the tiles to the ground (on bound sub grounds, cement, asphalt, ...). When glueing side to side allow gap surrounding the area for movement of tiles.

We reserve the right to improve the products. July 2007

Siemensring 25
53925 Kall
Deutschland

Tel. +49 (0)2441 5037
Fax +49 (0)2441 5039

info@err-team.de

more ...
Information,
examples of use,
installation guidelines &
Tips at:

www.err-team.de