

Rubber-Terrace-Tile „Eifel“



Dimensions	1010 x 1010 mm
Thickness	16 mm
Weight	15 kg
Material	Polyurethane bound rubber granules, cut surface, smooth feel
Standard Colours	1. light basis-colour (white-grey-black, marble effect)* 2. black basis-colour (black-grey-white, marble effect) Other colours can be provided on request.
Surface-Design	Cruciform-Design (optical effect of 50 x 50 cm tiles)
Underbody	Flat
Requirements	bound subgrounds with a slope, (e.g.cement, asphalt), water should be able to freely flow away from the area.

Places of use: terraces, club-terraces (e.g. golf)

Installation/Assembling: „Eifel“ must be fully adhered to the substrate (cement, asphalt, h-blocks). Cutting by hand held utility knife or electric hand saw with a smooth blade. Pay attention to measurement tolerances prior to and while assembling.

Recommended PU-glue: Type 1174. Amount of glue needed: Full adhesion with 1174: app. 350 gr. / m²

Tolerances and note about material: Tolerance in thickness: +/- 2 mm, Tolerance in dimension: +/- 1,5 %.

Rubber-tiles react to changes in temperature and humidity. This reaction can mostly be prevented by fully adhering the tiles to the ground.

*The amount of light colours (white, light grey, middle-grey) may vary in their percentage used from m² to m². This is due to the „recycling character“ of the granules.