

### Rubber-Terrace-Tile „Elegance“



<b>Dimensions</b>	1010 x 1010 mm
<b>Thickness</b>	20 mm
<b>Weight</b>	18 kg
<b>Material</b>	Polyurethane bound rubber granules with 4 inlays of high-density rubber sheets
<b>Colours</b>	1. light basis colour (white-grey-black, marble effect)* 2. black basis colour (black-grey-white, marble effect) Other colours can be provided on request.
<b>Surface Design</b>	Cruciform-Design (optical effect of 50 x 50 cm tiles)
<b>Underbody</b>	Flat
<b>Requirements</b>	bound subgrounds with a slope, (e.g.cement, asphalt), water should be able to freely flow away from the area.

**Places of use:** terraces, club-terraces (e.g. golf)

**Installation/Assembling:** „Eifel“ must be fully adhered to the substrate (cement, asphalt, h-blocks). Cutting by hand held utility knife or electric hand saw with a smooth blade. Pay attention to measurement tolerances prior to and while assembling.

**Recommended PU-glue:** Type 1174. Amount of glue needed: Full adhesion with 1174: app. 350 gr. / m<sup>2</sup>

**Tolerances and note about material:** Tolerance in thickness: +/- 2 mm, Tolerance in dimension: +/- 1,5 %.

Rubber-tiles react to changes in temperature and humidity. This reaction can mostly be prevented by fully adhering the tiles to the ground.

\*The amount of light colours (white, light grey, middle-grey) may vary in their percentage used from m<sup>2</sup> to m<sup>2</sup>. This is due to the „recycling character“ of the granules.

*We reserve the right to improve the products. July 2007*

Siemensring 25  
53925 Kall  
Germany

Tel. +49 (0)2441 5037  
Fax +49 (0)2441 5039

info@err-team.de

more ...  
Information,  
examples of use,  
installation guidelines &  
Tips at:

[www.err-team.de](http://www.err-team.de)