

Wall Mat „Soft“



	„Soft20“	„Soft30“
Dimensions	1010 x 1010 mm	1010 x 1010 mm
Thickness	20 mm	30 mm
Weight	15 kg	21 kg
Surface-Material	Polyurethane bound rubber granules, light coloured EPDM-Rubber-Granules, high density	
Bottom-Material	black foamed rubber, high density	
Surface Colour	light (white-grey-black, marble effect)	
Bottom Colour	Black	
Surface-Design	Flat	
Bottom	Flat	
Requirements	Walls, possible to drill, wood (waterproof)	

Places of use: Stable walls that require protection or any other walls that endanger the horse.

Installation/Assembling: Screwing or gluing to walls. Alternatively the tiles can be glued to a waterproof piece of wood lying on the ground – this structure can afterwards be screwed to the wall. Additionally glue side to side. Pay attention to installation-sheet. Recommended glue: SH100

Tolerances and note about material: * Tolerances in thickness: +/- 3 mm, *Tolerances in measurement: +/- 2 %
Rubber-Tiles expand under warm conditions and shrink in cold conditions. This reaction can be prevented by fully adhering the tiles to the subground.

We reserve the right to improve the products. July 2007

Siemensring 25
53925 Kall
Germany

Tel. +49 (0)2441 5037
Fax +49 (0)2441 5039

info@err-team.de

more ...
Information,
examples of use,
installation guidelines &
Tips at:

www.err-team.de