

Weight Lifting Tile ELEFANT



<i>Article number</i>	8ELEFANTx
<i>Thickness</i>	40mm
<i>Dimensions</i>	101x101 cm
<i>Installation</i>	These tiles are installed loose in indoor areas. Install in some kind of frame (e.g. wooden frame). Gluing is possible.
<i>Unit</i>	m ²
<i>Weight / Unit (kg)</i>	39 kg
<i>Surface design</i>	without design, chamfer on all sides
<i>Bottom design</i>	flat
<i>Standard colours</i>	black, redbrown

<i>Material</i>	Polyurethan bound rubber granules, surface material is high quality black EPDM-Rubber-Granules
<i>Tolerances</i>	length and width +/- 2%, thickness +/-2mm
<i>Resilience</i>	up to 150 kg

Glues (e.g.) For full glue down on cement, asphalt (or similar) use PU1174 (app. 500 gr. / m²). For side to side gluing use PU OC500 (app. 30 ml per running meter). Pay attention to installation guidelines.

Cleaning Avoid great amounts of dirt on the rubber mat by using appropriate solutions in all entrance areas. The rubber mats can be vacuum / broom cleaned. If using water and a mild detergent make sure to only use a moist but not totally wet cloth. Too much water could be soaked under the mats.
For the same reason, spilled liquids need to be removed in a timely manner.