

## Rubber Paddock Tile HT42WA

---



Article number	8HTx42WA
Thickness	42 mm (+ / - 2mm)
Dimensions	app. 1010 x 1010 mm (+ / - 2%)
Installation	loose
Unit	m <sup>2</sup>
Weight / Unit (kg)	43 kg
Surface design	without design, chamfered on all sides
Bottom design	flat (with water drainage canals)
Standard colour	black-mixed coloured
Special colours	redbrown, green, blue (min. order 75 m <sup>2</sup> )
Material	polyurethane bound rubber granules
Tolerances	length and width +/- 2%, thickness +/-2mm
Requirements	Compacted grounds, e.g. min. 20 cm of crushed gravel 1-16 mm and top layer of finer gravel 0 – 8 mm
Installation	As a top layer we recommend crushed gravel of 0 - 8 mm. The layer should be at least 8 cm thick. Depending on the load the 30 mm or 40 mm version are used. While most of the times the mats are laid loose they can also be glued to each other or - if used on concrete - they can be glued to the ground. Larger areas require a curbing or finished edge. Cutting the mats is easy by using a fret-saw or handheld utility knife (for smaller areas).
Cleaning	Clean thoroughly about twice a year using a high pressure cleaner. Put the cleaner to medium strength only.