

## Rubber Stable Tile Fantastic60



<i>Article number</i>	8HTEx60MF
<i>Thickness</i>	60 mm (+ / - 2mm)
<i>Dimensions</i>	app. 1010 x 1010 mm (+ / - 2%)
<i>Installation</i>	loose
<i>Unit</i>	m <sup>2</sup>
<i>Weight / Unit (kg)</i>	44 kg
<i>Surface design</i>	without design, chamfered on all sides
<i>Bottom design</i>	„feet-structure“, similar to the design of an egg-carton
<i>Standard colours</i>	grey
<i>Special colours</i>	redbrown, black-colour mix, green, blue (min. order 50 m <sup>2</sup> )
<i>Material</i>	polyurethane bound rubber granules
<i>Tolerances</i>	length and width +/- 2%, thickness +/- 2mm

For horses up to 700 kg

*Installation* The mats are installed lose in stalls - the weight of the mats and the walls will hold the mats in place. Mats can be cut with a hand held utility knife or better with a fret-saw. Due to the possible change in dimension (due to change in temperature and humidity) cutting may be necessary after some time.

*Cleaning* Depending on the amount of dirt on and especially under the mats, they need to be cleaned in regular intervals (at least twice a year from both sides). Remove all loose dirt under the mats and let a fair amount of water soak through the mats using a garden hose or a high pressure cleaner. Put the cleaner to medium strength only. Allow some hours for drying afterwards.

*Extras* Beveled edges for 60mm horse tiles,  
Dimensions: 1010x310 x 60/15mm

