

## Rubber-Roll S950



<i>Article number</i>	8S950SG10R
<i>Thickness</i>	10 mm
<i>Dimensions</i>	10m x 1,5m
<i>Unit</i>	rolls of 15 m <sup>2</sup>
<i>Weight / Unit (kg)</i>	app. 140 kg
<i>Materialdichte</i>	850 kg/m <sup>3</sup>
<i>Colour</i>	black-green
<i>Material</i>	polyurethane bound rubber granules and buffings
<i>Tolerances</i>	length and width: +/- 1%, thickness: +/- 1%
<i>Tensile strength</i>	1,15 N/mm <sup>2</sup> DIN 53571, test piece B
<i>Elongation of break</i>	90 % DIN 53571, test piece B
<i>Temperature Range</i>	-40 °C to 115 °C
<i>Fire Class</i>	B2 DIN 4102
<i>Installation</i>	Install by using lathes or fix by gluing to the ground (cement, asphalt, ...) Ask a qualified professional to install if gluing is needed. The rolls need to be unrolled upside-down (against the way it has been rolled) for a period of no less than 24 hours in the temperature area where they will be finally installed. Suitable glues are PU- or Dispersion-Glues from Henkel, Uzin, Forbo ...) Test gluing on problematic surfaces is always recommended.
<i>Glues</i>	SIKA (SikaBond T8, T45, T52FC, T54FC, T55), Klebag (Kleapur PU 900), Wakol (PU 270), Uzin Tyro (UZIN-KR 421), Thomsit K188E,
<i>Gluing tape (e.g.)</i>	e.g. D-Tack Extra-Lay
<i>Surface coating</i>	Longer colour intensity, a silk-matt gloss and better cleaning performance can be achieved by using e.g. RZ Turbo Protect Plus.