

Sport-artificial grass tile „Supergras“



<i>Article number</i>	8SKGP45H / 8SKGP35H
<i>Thickness</i>	35 mm / 45 mm
<i>Dimensions</i>	50x50 cm
<i>Installation</i>	Loose installation in evenly tempered interiors. Edged by rails (or similar) in the event of possible tensile forces (e.g. weight sled). Gluing (on the side or over the entire surface) is possible.
<i>Installation mats can be fitted with connectors.</i>	
<i>Unit</i>	¼ m ²
<i>Weight / Unit (kg)</i>	18,5 kg (35mm) / 28,0 kg (45mm)
<i>Water permeable</i>	yes
<i>Surface design</i>	-
<i>Bottom design</i>	flat
<i>Colour</i>	green
<i>Material elastic layer</i>	SBR rubber granules, PU bound
<i>Material top layer</i>	Artificial grass made of polypropylene, app. 7500/1 dTex, 14mm thick, app. 40.000 stitches / m ²
<i>Tolerances</i>	length and width +/- 2%, thickness +/-2mm
<i>Chem. Behavior</i>	Resistant to water, many diluted acids and alkalis; chemically neutral, UV-resistant, frost-proof
<i>Laying direction</i>	In order to achieve a uniform color image, all tiles should be laid out in the direction of the pile. Using a small test area for your lighting situation, check which appearance you like best before laying.
<i>Glues (optional)</i>	Full-surface bonding: PU 1174, 1 kg bottles, consumption app. 500 g / m ² Side-to-side gluing: PU OC500, 310ml cartridges, consumption app. 30 ml / running meter
<i>Cleaning</i>	Due to production, there may be loose synthetic grass fibers on the panels supplied. These can easily be removed with a vacuum cleaner. Regular cleaning is also carried out using a vacuum cleaner.