

## Weight Lifting Tile Taff

---



<i>Article number</i>	8TAFF40
<i>Thickness</i>	40mm
<i>Dimensions</i>	101x101 cm
<i>Installation</i>	These tiles are installed loose in indoor areas. Install in some kind of frame (e.g. wooden frame). Gluing is possible.
<i>Unit</i>	m <sup>2</sup>
<i>Gewicht / Mengeneinheit (kg)</i>	38 kg
<i>Surface design</i>	without design, chamfer on all sides
<i>Bottom design</i>	flat
<i>Standard colour</i>	redbrown
<i>Special colours</i>	green, black, blue, grey (min. order 50m <sup>2</sup> )
<i>Material</i>	Polyurethane bound rubber granules, surface material is high quality black EPDM-Rubber-Granules
<i>Tolerances</i>	length and width +/- 2%, thickness +/-2mm
<i>Resilience</i>	up to 100 kg
<i>Glues (e.g.)</i>	For full glue down on cement, asphalt (or similar) use PU1174 (app. 500 gr. / m <sup>2</sup> ). For side to side gluing use PU OC500 (app. 30 ml per running meter). Pay attention to installation guidelines.
<i>Cleaning</i>	Avoid great amounts of dirt on the rubber mat by using appropriate solutions in all entrance areas. The rubber mats can be vacuum / broom cleaned. If using water and a mild detergent make sure to only use a moist but not totally wet cloth. Too much water could be soaked under the mats. For the same reason, spilled liquids need to be removed in a timely manner.