



<i>Article number</i>	8VUM2 / 8VUM70	
<i>Granule size</i>	fine grain: 0,5-2,5mm / rough grain: 1-4mm	
<i>Colour</i>	black-mixed-coloured	
<i>Weight</i>	33kg per set	
<i>m<sup>2</sup> per kit</i>	3m <sup>2</sup> in 10mm, 2m <sup>2</sup> in 15mm, 1,5m <sup>2</sup> in 20mm	
<i>Unit</i>	kits of granules, polyurethane-binder, primer	
<i>Material</i>	Pre-treated rubber-granules/ polyurethane-binder. The cured product is open-pored	
<i>Working-time</i>	Install mixtures within 15-30 minutes.	
<i>Storage</i>	PU-binder app. 6 months, rubber granules app. 36 months	
<i>Requirements</i>	Install only at temperatures of more than 10 degrees C. Apply in well ventilated areas. No form of moisture (rain, fog, snow are to be present while assembling and at least 24h after assembling. Bound subground, e.g. wood, metal, cement, use double amount of primer on absorbent surfaces. Test the material on problematic surfaces.	
<i>Cleaning</i>	Use a garden hose or a high pressure washer in regular intervals (3 month recommended). Put the pressure washer to medium strength only.	
<i>Installation</i>	1. Pre-treatment of floor with primer 1103. Let dry for 4 – 6 h. 2. Mix 5 kg of granules and 1 kg of binder for min. 3 minutes. 3. Supply evenly on floor by using a lath suitable to reach the required thickness. 4. Compress by using a trowel or suitable tool. 5. Continue from point 2 until area is finished 6. Let dry for min. 24 hours until finished. A detailed installation-sheet is provided with every delivery.	
<i>Places of use and recommended thickness</i>	Horse transporters / stall aisles	10 mm
	Wash racks / chutes	15 mm
	Guiding circles	20 mm

*Note about material* Colour differences between kits may occur, due to the recycling character of the material. We recommend to mix different kits, especially for larger areas.