




## Solid Rubber Mat XXL



<i>Article number</i>	9GM12090XXLP
<i>Thickness</i>	17 mm
<i>Dimensions</i>	app. 120 x 90 cm when it's 20 degree celsius: A = 121 cm, B = 91 cm, width puzzle connectors= 2,5 cm width of the edge profiles incl. connectors= 8,5 cm
<i>Installation</i>	loose, screwing possible
<i>Unit</i>	pcs. (1,08 m <sup>2</sup> )
<i>Weight / Unit (kg)</i>	20 kg
<i>Surface design</i>	raindrop pattern
<i>Bottom design</i>	8mm lengthwise profile
<i>Standard colours</i>	black
<i>Material</i>	rubber
<i>Tolerances</i>	length and width +/- 1%, thickness +/-2mm
<i>Fire Class (EN 13501-1:2010)</i>	<b>E<sub>fl</sub></b>
<i>Installation</i>	Let mats adjust to room temperature for 24 hours. Place puzzle connectors over each other and step on the connectors – or use a rubber hammer. Use some kind of alignment to receive straight area outlines. Leave app. 1-2cm from each connecting wall since rubber tiles are likely to expand. Cut by using a fret saw or a carpenter knife.
<i>Cleaning</i>	Avoid great amounts of dirt on the rubber mat by using appropriate solutions in all entrance areas. The rubber mats can be vacuum / broom cleaned. If using water and a mild detergent make sure to only use a moist but not totally wet cloth. Too much water could be soaked under the mats. For the same reason, spilled liquids need to be removed in a timely manner.
<i>Extras</i>	Puzzle connectors all around the mat, edge profiles available (tapered edges 17 to 1 mm, 85 mm wide)