

# DATASHEET

## Rubber-Roll T980



<i>Article number</i>	9T980
<i>Thickness</i>	10 mm
<i>Dimensions</i>	10m x 1,25m
<i>Unit</i>	rolls of 12,5 m <sup>2</sup>
<i>Weight / Unit (kg)</i>	app. 120 kg
<i>Density</i>	980 kg/m <sup>3</sup>
<i>Colours</i>	black - with mix of 5, 10 or 20% colour EPDM – min order 200 m <sup>2</sup> / colour mix
<i>Material</i>	recycling rubber granules and EPDM granules, PU bound
<i>Tolerances</i>	length and width +/- 1,5%, thickness +/-5%
<i>Tearresistance</i>	>1,5 (DIN 53455)
<i>Force reduction</i>	app. 14%
<i>Temperature Range</i>	-30 to +80°C
<i>Linear thermal expansion</i>	23,1*10 <sup>-5</sup> /°C +3,4% (following DIN 53752)
<i>Thermal conductivity</i>	0,17W/(mK) EN 12667
<i>Fire class</i>	E <sub>fl</sub> (normal, old B2) EN 13501
<i>Sound improvement</i>	ca. 18 dB (depending on construction)
<i>Anti-Slip Property</i>	R10 (DIN 51130); μ 0,57 EN 13893
<i>Electrical Properties</i>	-0,7 kV (antistatic)
<i>Vapour diffusion</i>	Vapour permeable
<i>Chem. Behaviour</i>	Resistant to water, numerous diluted acids and alkaline solutions; chemically neutral; UV resistant. (EN423)
<i>Installation</i>	See separate installation sheet available upon request – ask your qualified floor layer for advise.
<i>Glues (e.g.)</i>	SIKA (SikaBond T8, T45, T52FC, T54FC, T55), Klebag (Klebagur PU 900), Wakol (PU 270), Uzin Tyro (UZIN-KR 421), Thomsit K188E,
<i>Gluing tape</i>	e.g. D-Tack Extra-Lay

**Also available as puzzle tiles of 60 x 60 cm.**